# **CTM POTTERS SUPPLIES**

## SAFETY DATA SHEET

#### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### **Product information:**

Product Name : Colemanite

Chemical Name : None

Synonyms : None

Company : CTM Potters Supplies

Unit 10A, Millpark Industrial Estate

White Cross Road Woodbury Salterton

Woodbury Salter Nr. Exeter

EX5 1EL
Telephone : 01395-233-077
Fax : 01395-233-905

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS Number	EC Number	% of composition
Colemanite standard	12291-65-5		100%
Ceramic frit (ground)	65997-18-4		100%

## 3. HAZARD IDENTIFICATION

Inhalation: Excessive exposure may cause symptoms of chronic lung disease.

**Ingestion:** The product is of low solubility in body fluids and it is likely to be of low acute toxicity.

Eyes: May cause physical irritation and inflammation.

**Skin:** The material is not a primary irritant, but as with any abrasive powder it may give rise to minor irritation.

## 4. FIRST AID MEASURES

## **General Recommendations:**

**Inhalation:** Remove patient to fresh air, loosen tight clothing and seek medical attention.

**Ingestion:** Do not induce vomiting. Seek medical advice.

Eyes: Wash immediately with copious amounts of water.

**Skin:** Wash affected areas with water.

## 5. FIRE-FIGHTING MEASURES

Extinguishing media: It is compatible with standard fire fighting technique (e.g. use of water, carbon dioxide, dry

powder, sand and chemical foam extinguishers.

Special exposure hazards: None

**Protective personal equipment:** None other than those suitable for the surrounding fire conditions.

#### 6. ACCIDENTAL RELEASE MEASURES

Leaks & Spills: Collect dry material by wet sweeping or vacuum with efficient particulate filter.

**Personal protective equipment:** Respiratory protective equipment.

7. HANDLING AND STORAGE

**Handling:** Do not eat, drink, or smoke in areas where the material is used.

Wash thoroughly after handling the material.

**Storage:** Store in dry area.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering controls:** Adequate ventilation should be provided so that Occupational Exposure Limits are not

exceeded. Local Exhaust Ventilation is normally recommended.

**Personal protective equipment:** Where LEV is not practicable and exposure is likely to be excessive, approved respiratory

protection to CEN standards prEN 140, 141, 143 or 149 should be worn. Protective gloves

and overalls are recommended for prolonged contact.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form: powder Colour: off white Odour: odourless

Flash point (<sup>0</sup>C): N/A

Flammability: Not known

Explosive properties: Non-explosive

Oxidising properties:

Specific gravity:

2-3

pH value:

9.3

Melting point (°C): 930°C- between 900°C and 1180°C

## 10. STABILTY AND REACTIVITY

**Chemical stability:** The material is stable.

Conditions/materials to avoid: None known

Hazardous decomposition products: None known

Hazardous polymerization products: None

## 11. TOXICOLOGICAL INFORMATION

Acute toxicology: LD<sub>50</sub> Oral (rats): >2000mg/kg

LD<sub>50</sub> Dermal: Not known LD<sub>50</sub> inhalation: Not known

Health effects: Prolonged or repeated exposure above Occupational Exposure Standards may

cause fibrosis of the lungs.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** Not known.

**Persistence:** The product is chemically stable and will persist in the environment.

## 13. DISPOSAL CONSIDERATIONS

Dispose in accordance with current waste disposal regulations (for UK – Control of Pollution (Special Waste) Regulations 1996). Landfill is the most appropriate method.

#### 14. TRANSPORT INFORMATION

UN/SI No. None UN Class Not restricted Packing Group Not restricted Road UK Not restricted ADR Not restricted Sea IMO Not restricted Air Not restricted

**ICAO** 

#### 15. REGULATORY INFORMATION

EC Supply Labelling: None required by directive 88/379/EEC

R-Phrases: None

S-Phrases: Optional for dusty powders

S20/21 when using do not eat, drink or smoke.

S38 in case of insufficient ventilation wear suitable respiratory equipment.

**UK Occupational exposures limits\*:** Mg/m<sup>3</sup> 8 hr TWA % in product.

In accordance with HSE Approved Code of Practice for CHIP, the recipient is reminded of their obligations under both the Health and Safety at Work Act (HSWA) and the Control of Substances Hazardous to Health Regulations (COSHH), and that the information in any safety data sheet does not constitute the user's assessment of workplace risk.

#### 16. OTHER INFORMATION

#### References:

COSHH ACOP HSC approved Code of Practice for the Control of Substances Hazardous to Health Regulations 1994

CHIP 96 Chemicals (Hazard Information and Packaging for Supply) Regulations 1996

CHIP SDS ACOPS HSC Approved Code of Practice for Safety Data Sheets in accordance with regulation 6 of the CHIP

regulations.

HSE EH40 HSE Guidance note EH40 on Occupational Exposure Limits to be used in conjunction with the COSH

regulations.

## **Further information:**

Data sheet producing department: CTM Potters Supplies

Telephone: 01395-233-077

#### Disclaimer:

The information contained in this safety data sheet has been prepared using the best available information, however in view of technical developments, this may alter. The material must only be used for its stated purpose and the information contained within this data sheet is offered solely for use in the evaluation of this product in respect of safety, health and environmental hazards. Due to the many factors outside our control when using this product, we cannot accept liability for any injury, accident, loss or damage caused through its use.

<sup>\*</sup>Refer to HSE Guidance note EH40